



Kitchen. Design & Technology

Diamant Induction cooktop

MADE IN
GERMANY

Product information

The side-by-side cooking zones bring maximum space and convenience to your kitchen while cooking. The extractor fan is integrated in the rear part of the cooktop and therefore does not take up any space. The motor is embedded directly

Every cook top with booster

The boost function increases the power of the selected cooktop for a short time and allows you to reach the maximum temperature faster.

Integrated fume cupboard as plug-in solution

Thanks to its compact design, installing the cooktop is child's play. This means less planning effort is required.

Four cooking zones side by side

A tidy way to cook. With four cooking hobs side by side, pushing pots back and forth is a thing of the past.

Bridge function and temperature zones

With the help of the bridge function, 2 fields can be coupled. This means that even larger roasters can be easily accommodated. Defined temperature levels allow you to grill vegetables, meat and fish at the optimum temperature.

Product data

Design:

Flush & surface mounting possible
Narrow & compact dimensions
Modern cooking zone labeling

Features & Functions:

Max. space on the cooktop
Clear cooktop layout
Interactive Flex Slider Touch
Automatic boil-on function
Automatic pot detection
Timer
Melt setting 42°, heat holding setting 70°, simmer setting 94°
Grill function
Pause & recall function
Stainless steel filter dishwasher safe
Integrated automatic ventilation control in 10 steps with slider
Filter change indicator
Increased space
Easy cleaning
Stainless steel components for more hygiene
Activated carbon exchangeable from above (optional accessory)

Safety:

Interlock, child safety lock, safety shutdown,
Sensor circuit / Flex Slider, residual heat indicator

Included:

Induction cooktop
Power cable
Stainless steel grease filter
Sealing strip
Cooking tongs
Microfibre cloth
Cover grill
Instructions for use and assembly
Care instructions

Unit dimensions (W x H x D) & weight (kg):

980 × 212 × 520 mm
33 kg

Cutout dimensions (W x D):

960 × 490 mm

Cooking zones:

2 induction cooking zones

190 × 220 mm, 2,1/3,7 kW

2 induction cooking zones

190 × 220 mm, 2,1/3,5 kW

Bridge function

390 × 220 mm, 3,7 kW

Connection values:

Voltage AC 220-240 V / 2NAC 400 V, 50/60 Hz
Power 7,4 kW

Technical data pedestal fan:

Operating mode: circulation or extraction

Max. power: 605 m³/h

Motor: 168 W

Control: 9 levels+ Power
+ run-on function

Air output motor: NW 150

Operating noise: min. 33 dBA / max. 62 dBA

Grease separation: 98,5 %

Grease separation Claas: A

Accessories:

Air extraction set (9500000370)

Recirculation set carbon filter in base (9500000371)

Recirculation set charcoal filter with socket cover (9500000372)

Plasma filter in socket (9500000387)

Plasma filter back panel (9500000388)

Honeycomb carbon filter (9500000385)

Technical drawings

