



Kitchen. Design & Technology

Onyx Induction cooktop



Product information

Technically and stylishly on the highest level, that's how is how Onyx presents itself. The operation via the high-quality knobs is especially in high-end design kitchens again fully trendy and is not only practical, but lets you feel like a pro.

Bridge function and temperature zones

With the help of the bridge function, 2 fields can be coupled. This means that even larger roasters can be easily accommodated. Defined temperature levels allow you to grill vegetables, meat and fish at the optimum temperature.

High quality knob control

Selected details, such as the high-quality stainless steel knobs, enhance your kitchen. This is how we bring the feeling of professional cooking to your home.

Integrated fume cupboard as plug-in solution

Thanks to its compact design, installing the cooktop is child's play. This means less planning effort is required.

Maximum space

The division of the cooktop allows you to use pots of any size – no matter on which cooking zone.

Product data

Design:

Flush & surface mounting possible
Narrow & compact dimensions
Modern cooking zone labeling

Features & Functions:

Max. space on the cooktop
Clear cooktop assignment through toggle control
Power level for each cooking zone
Bridge function on the right
Automatic boil-on function
Automatic pot detection
Pause & recall function
Melt setting 42°, heat holding setting 70°, simmer setting 94°
Integrated automatic ventilation in 10 steps with toggle control
Energy-saving EC fan
Filter change indicator
Increased space
Easy cleaning
Activated carbon exchangeable from above (optional accessory)

Included:

Induction cooktop
Power cable
Stainless steel grease filter
Sealing strip
Cooking tongs
Microfibre cloth
Cover grill
Instructions for use and assembly
Care instructions

Safety:

Interlock, child safety lock,
Safety shut-off, residual heat indicator

Unit dimensions (W x H x D) & weight (kg):

800 × 212 × 520 mm
27 kg

Cutout dimensions (W x D):

750 × 500 mm

Cooking zones:

2 induction cooking zones

190 × 220 mm, 2,1/3,5 kW

Bridge function

390 × 220 mm, 3,5 kW

1 induction cooking zone

Ø 210, 2,3/3,7 kW

1 induction cooking zone

Ø 180, 1,85/3,0 kW

Connection values:

Voltage AC 220-240 V / 2NAC 400 V, 50/60 Hz
Power 7,4 kW

Technical data pedestal fan:

Operating mode:	circulation or extraction
Max. power:	570 m ³ /h
Motor:	168 W
Control:	9 levels+ Power + run-on function
Air output motor:	NW 150
Operating noise:	min. 35 dBA / max. 70 dBA
Grease separation:	98,4 %
Grease separation Claas:	A

Accessories:

Air extraction set (9500000370)
Recirculation set carbon filter in base (9500000371)
Recirculation set charcoal filter with socket cover (9500000372)
Plasma filter in socket (9500000387)
Plasma filter back panel (9500000388)
Honeycomb carbon filter (9500000385)

Technical drawings

